

1. Identification

1.1 Product Identifier

Product Name: Methanol
CAS Number: 67-56--1

1.2 Relevant Identified Uses of the substance and Uses Advised Against

Product Use: Industrial Applications
Uses Advised Against: Not for use in final consumer products

1.3 Details of the supplier/manufacturer

Manufacturer/Supplier: Purification Technologies, Inc. (PTI)
67 Winthrop Rd., Chester, CT 06412

General Assistance: 860-526-7801 (Mon-Fri, 8:30 am to 5:00 pm)

1.4 Emergency Telephone Number:

24-hr Emergency Number CHEMTREC: In USA: 800-424-9300
Outside USA: 703-527-3887

2. Hazards Identification

GHS Classification: Flammable liquids (Category 2)
Acute Toxicity, Oral (Category 3)
Acute Toxicity, Inhalation (Category 3)
Acute Toxicity, Dermal (Category 3)
Specific target organ toxicity – single exposure (Category 1)

Category Key:
Category 1: Most dangerous
Category 4: Least severe

Label elements:

Pictogram



Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor
H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled
H370 Causes damage to organs

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge.

P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310 + P330	IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P311	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
P307 + P311	IF exposed: Call a POISON CENTER or doctor/physician
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	% Weight
Methanol	67-56-1	100.0%

4. FIRST AID MEASURES

Inhalation:

Remove individual away from exposure and into fresh air. If breathing is difficult, administer oxygen if available or give artificial respiration. Keep person warm and quiet; seek immediate medical attention.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin:

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Notes to Physicians: This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is

required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, central nervous system, pancreas, heart. Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias.

5. FIREFIGHTING MEASURES

Flashpoint: 54.0°F (12.2°C) CC

Lower Explosive Limit in air, % by volume: 6.0

Upper Explosive Limit in air, % by volume: 36.0

Autoignition Temperature: 867°F (464°C)

Flammable Liquid and Vapor!

Hazardous Products of Combustion: May form carbon dioxide and carbon monoxide.

Fire and Explosion Hazards: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. During a fire, irritating or toxic decomposition products may be generated.

Extinguishing Media: Alcohol foam, carbon dioxide, dry chemical.

Firefighting Instructions: Water may be ineffective. Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating:

Health: 1

Flammability: 3

Reactivity: 0

6. ACCIDENTAL RELEASES MEASURES

Ventilate area of spill.

Small Spill: Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other

bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product utilizing inert material (vermiculite, dry sand, earth). Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

7. HANDLING AND STORAGE

Handling:

Protect against physical damage. Store in a cool, dry, well-ventilated location, away from any area where fire hazard may be acute. Outside or detached storage is preferable. Storage and use areas should be No Smoking areas. Containers of this material may be hazardous when emptied. Since emptied container retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/or bonded when material is transferred. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death.

WARNING:

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection: If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air-supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Ingredient	OSHA PEL	OSHA VPEL		ACGIH TLV	
	TWA	TWA (skin)	STEL (skin)	TWA (skin)	STEL(skin)
Methanol 67-56-1	200 ppm	200 ppm	250 ppm	200 ppm	250 ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

<p>Boiling Point: 147.0°F(63.8°C) @ 760 mmHg Vapor Pressure: 97.680 mmHg @ 68.00°F Specific Vapor Density: 1.110 @ AIR=1 Specific Gravity: .792 @ 68.00°F Liquid Density: 6.600 lbs/gal @ 68.00°F 0.792 kg/l @ 20°C % Volatile: 100.0% Volatile Organic Compounds: 100.00% 795.00 g/l 6.630 lbs/gal Bulk Density: 0.890 lbs/ft³</p>	<p>Evaporation Rate: 2.10 (N-Butyl Acetate) Appearance: Clear, mobile State: Liquid Physical Form: Neat Color: Colorless Odor: Mild Alcohol pH: No Data Viscosity: 0.6 cps Freezing Point: -144.00 ° F (-97.7 °C) Molecular Weight: 32.04 % Solubility in Water: Complete</p>
---	--

10. STABILITY AND REACTIVITY

Hazardous Polymerization: Product will not undergo hazardous polymerization.

Hazardous Decomposition: May form: carbon dioxide, carbon monoxide and formaldehyde when heated to decomposition.

Chemical Stability: Stable under ordinary conditions of use and storage..

Incompatibility: Avoid contact with: calcium hypochlorite, hypochlorites, peroxides, sodium, strong acids, strong bases, strong oxidizing agents, zinc.

11. TOXICOLOGICAL INFORMATION

Methyl Alcohol (Methanol) Oral rat LD50: 5628 mg/kg; inhalation rat LC50: 64000 ppm/4H; skin rabbit LD50: 15800 mg/kg; Irritation data-standard Draize test: skin, rabbit: 20mg/24 hr. Moderate; eye, rabbit: 100 mg/24 hr. Moderate. Investigated as a mutagen, reproductive effector.

-----\Cancer Lists\-----			
	---NTP Carcinogen---		
Ingredient	Known	Anticipated	IARC Category

Methyl Alcohol (67-56-1)	No	No	None

12. ECOLOGICAL INFORMATION

Environmental Fate:

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material is expected to quickly evaporate. When released into the water, this material is expected to have a half-life between 1 and 10 days. When released into water, this material is expected to readily biodegrade. When released into the air, this material is expected to exist in the aerosol phase with a short half-life. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into air, this material is expected to have a half-life between 10 and 30 days. When released into the air, this material is expected to be readily removed from the atmosphere by wet deposition.

Environmental Toxicity:

This material is expected to be slightly toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. TRANSPORT INFORMATION

U.S. Department of Transportation (DOT) 49 CFR 172.101

Proper Shipping Name: Methanol

Hazard Class: 3

UN/NA Code: UN1230

Packing Group: PG II

Bill of Lading Description: Methanol, 3, UN 1230, PGII

Labels Required: Flammable Liquid

Placards Required: Flammable Liquid

NOS Component: None

RQ (Reportable Quantity), 49 CFR 172.101

Product Quantity (lbs): 5000

Component: Methanol

Other Transportation Information: The DOT Transport Information may vary with the container and mode of shipment.

15. REGULATORY INFORMATION

-----\Chemical Inventory Status - Part 1\-----
Ingredient TSCA EC Japan Australia

SDS Code: PTI001
 Effective Date: 2/16/15

Methyl Alcohol (67-56-1)	Yes	Yes	Yes	Yes
-----\Chemical Inventory Status - Part 2\-----				
Ingredient	Korea	DSL	NDSL	Phil.
Methyl Alcohol (67-56-1)	Yes	Yes	No	Yes
-----\Federal, State & International Regulations - Part 1\-----				
Ingredient	-SARA 302- RQ	TPQ	-----SARA 313----- List	Chemical Catg.
Methyl Alcohol (67-56-1)	No	No	Yes	No
-----\Federal, State & International Regulations - Part 2\-----				
Ingredient	CERCLA	-RCRA- 261.33	-TSCA- 8(d)	
Methyl Alcohol (67-56-1)	5000	U154	No	

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
 SARA 311/312: Acute: Yes Chronic: Yes Fire: Yes Pressure: No
 Reactivity: No (Pure / Liquid)

Australian Hazchem Code: 2PE
Poison Schedule: S6
WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

International Regulations
Inventory Status

- AICS (Australia)** The international ingredients of this product are listed.
- DSL (Canada)** The international ingredients of this product are listed.
- ECL (South Korea)** The international ingredients of this product are listed.
- EINECS (Europe)** The international ingredients of this product are listed.
- ENCS (Japan)** The international ingredients of this product are listed.
- IECSC (China)** The international ingredients of this product are listed.
- PICCS (Philippines)** The international ingredients of this product are listed.

State and Local Regulations

California Proposition 65: None.
New Jersey RTK Label Information: Methyl Alcohol 67-56-1
Pennsylvania RTK Label Information: Methanol 67-56-1

16. OTHER INFORMATION

NFPA Ratings: Health: **1** Flammability: **3** Reactivity: **0**

Product Use:

Laboratory Reagent.

Disclaimer

Information contained in this publication, while accurate to the best of the knowledge and belief of Purification Technologies, Inc., is not intended and should not be construed as a warranty or representation for which Purification Technologies, Inc. assumes legal responsibility.

Any information or advice obtained from Purification Technologies, Inc. otherwise than by means of this publication and whether relating to Purification Technologies, Inc. materials or other materials, is also given in good faith. However, it remains at all times the responsibility of the customer to ensure that Purification Technologies, Inc. materials are suitable for the particular purpose intended.

Insofar as materials not manufactured or supplied by Purification Technologies, Inc. are used in conjunction with or instead of Purification Technologies, Inc. materials, the customer should ensure that they have received from the manufacturer or supplier all technical data and other information relating to such materials.

Purification Technologies, Inc. accepts no liability whatsoever (except otherwise provided by law) arising out of the use of information supplied, the application, adaptation or processing of the products described herein, the use of other materials in lieu of Purification Technologies, Inc. materials or the use of Purification Technologies, Inc. materials with such other materials.